

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number
WO 2005/003665 A3

(51) International Patent Classification?: F27B 7/36,
F27D 7/04, B01F 5/04

(21) International Application Number:
PCT/IB2004/002209

(22) International Filing Date: 5 July 2004 (05.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2434380 4 July 2003 (04.07.2003) CA
2445818 21 October 2003 (21.10.2003) CA

(71) Applicant (for all designated States except US): HOLCIM
LTD. [CH/CH]; Zürcherstrasse 156, CH-8645 Jona (CH).

(72) Inventor; and

(75) Inventor/Applicant (for US only): LOWES, Thomas,
McQuiggin [GB/GB]; Spotlane, Bearstead, GB- Maid-
stone, Kent (GB).

(74) Agent: HAFFNER, Thomas, M.; Schottengasse 3a,
A-1014 Wien (AT).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

(88) Date of publication of the international search report:
21 April 2005

[Continued on next page]

(54) Title: METHOD AND SYSTEM FOR PROCESS GAS ENTRAINMENT AND MIXING IN A KILN SYSTEM



(57) Abstract: A method and system for mixing process gas flow by adding or injecting suitably-directed high momentum turbulent gas into dustladen stratified process gas flow at approximately 850 to 1400°C to entrain the process gas flow such that stratification is reduced and mixing of both gases and suspended solids is improved. The jet entrainment of the process gas flow by appropriate injection of gas serves to enhance the contact of reacting materials, such as residual fuel and available oxygen, and further serves to improve the completion of reactions, such as combustion of the fuel and the transfer of heat to the raw material/kiln feed.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.